



**In Union,
there is strength.**



U-CRYL SL-114

Revision Date: 08/19

RECOMMENDED FOR USE WITH:
Leather

U-CRYL SL-114 is a large particle size acrylic emulsion used for the impregnation of corrected grain leathers, or may be used in base coat systems. U-CRYL SL-114 is a medium-firm resin that is excellent for surface fine break improvement. U-CRYL SL-114 also has outstanding acetone and toluene resistance.

APPLICATION TYPES

Shoe

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 39 - 41

PH: 3.5 - 4.5

VISCOSITY @ 25 DEGREES C: 1 - 100 cps.

VOC (% OF TOTAL WEIGHT): 0

SPECIFIC GRAVITY: 1.01

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 18 months.

HARMONIZE TARIFF NUMBER: 3906.90.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
