



**In Union,
there is strength.**



UNISEAL 9049

Revision Date: 02/22

Reviewed:02/10/2022

RECOMMENDED FOR USE WITH:

Leather

UNISEAL 9049 is a slightly cationic pre-bottom for corrected grain leathers to give uniformity and filling properties. Pigment can be added to UNISEAL 9049 up to 10% for added coverage. Recommended use is to spray and then plate the leather prior to finishing. Suggested application method is to dilute and apply by spray method as follows (* Due to the chemical nature of this product, we recommend that UNISEAL 9049 be mixed for 30 minutes under medium shear before using.):

Water 40

Penetrator 10

Uniseal 9049 50

Pigment 2 - 10

APPLICATION TYPES

Upholstery, Shoe, Handbag, Waterproof

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 25 - 30

PH: 7.0 - 9.0

VISCOSITY @ 25 DEGREES C: 100-900 cps.

VOC (% OF TOTAL WEIGHT): 0

SPECIFIC GRAVITY: 0.97-1.0

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 12 months.

HARMONIZE TARIFF NUMBER: 3809.93.0000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
