



**In Union,
there is strength.**



UNITHANE 2783 NF

Revision Date: 06/21

Reviewed:06/21

RECOMMENDED FOR USE WITH:

Leather

UNITHANE 2783 NF is a NMP-free compact binder, which was developed to be soft and flexible and to give excellent fill and coverage for upgrading, as a sealer coat. UNITHANE 2783 NF has been used to replace "Stucco" type applications in splits, corrected grain and full grain leathers. This is a high performance resin package and is suitable for use in automotive, as well as non automotive applications. All additives should be adjusted to a pH of 7.0 - 8.0 before adding to the UNITHANE 2783 NF. For starting point formulas, contact your Union Specialties Inc. representative.

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Automotive, Aircraft, Upholstery, Shoe, Splits, Handbag

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 28 - 30

pH: 8.0 - 10.0

VISCOSITY @ 25 DEGREES C: 1000 - 3500 cps.

VOC (% OF TOTAL WEIGHT): 9.0-10.0

SPECIFIC GRAVITY: 1.01-1.04

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 12 months

MIX WELL BEFORE USING

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
