



***In Union,
there is strength.***



UNITHANE 2890 NF

Revision Date: 06/21

Reviewed:02/10/2026

RECOMMENDED FOR USE WITH:

Leather

UNITHANE 2890 NF is an NMP-Free low gloss compact binder, which is designed to be soft and flexible and give excellent fill/coverage for upgrading, as a sealer coat/basecoat. UNITHANE 2890 NF is also silica free although considered semi-matte due to dull urethane technology. This high performance resin package has excellent abrasion and flexing properties, along with molding/embossing definition. UNITHANE 2890 NF is ideal for leather (splits, corrected, full grain) and soft flexible synthetic materials.

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Dull, Automotive, Aircraft, Upholstery, Shoe, Splits, Handbag, Synthetic Leather

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 28 - 30

pH: 7.5 - 9.5

VISCOSITY @ 25 DEGREES C: 1000 - 3500 cps.

VOC (% OF TOTAL WEIGHT): 5.2-6.2

SPECIFIC GRAVITY: 1.01-1.04

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 12 months

MIX WELL BEFORE USING

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
