



**In Union,
there is strength.**



UNITHANE 351 NF

Revision Date: 06/21

Reviewed:

RECOMMENDED FOR USE WITH:

Leather

UNITHANE 351 NF is a medium/soft, lightfast, NMP-free waterborne polyurethane, designed for use as a resin binder for basecoats where it has superior elasticity and recovery adhesion, water resistance and abrasion resistance. UNITHANE 351 NF has good filling properties on porous substrates and very good compatibility with waterborne pigments and other additives that are commonly used in waterborne applications.

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Bright, Aircraft, Upholstery, Shoe, Splits, Handbag, Synthetic Leather

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 31 - 33

pH: 9.0 - 10.5

VISCOSITY @ 25 DEGREES C: 1 - 500 cps.

VOC (% OF TOTAL WEIGHT): 5.0-6.0

SPECIFIC GRAVITY: 1.01-1.04

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 12 months

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
