



**In Union,
there is strength.**

**MADE IN
USA**

UNITHANE AUM NF

Revision Date: 02/24

Reviewed:02/07/2024

RECOMMENDED FOR USE WITH:

Leather, Automotive Interiors - Leather

UNITHANE AUM NF a soft, aliphatic waterborne polyurethane made without NMP. UNITHANE AUM NF can be used as a basecoat or a topcoat resin, and has excellent cold crack resistance, as well as good abrasion resistance, heat resistance, and flexibility.

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Bright, Automotive, Aircraft, Upholstery

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 34 - 36

pH: 8.0 - 10.0

VISCOSITY @ 25 DEGREES C: 1 - 1000 cps.

VOC (% OF TOTAL WEIGHT): 8.0-8.3

SPECIFIC GRAVITY: 1.01-1.04

APPEARANCE: Opaque

GLOSS @60°: 70-100

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 12 months.

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
