



***In Union,  
there is strength.***



## **UNITHANE AUM NF**

Revision Date: 03/22

Reviewed:

### **RECOMMENDED FOR USE WITH:**

Leather, Automotive Interiors - Leather

UNITHANE AUM NF a soft, aliphatic waterborne polyurethane made without NMP. UNITHANE AUM NF can be used as a basecoat or a topcoat resin, and has excellent cold crack resistance, as well as good abrasion resistance, heat resistance, and flexibility.

### **SPECIAL FEATURES**

NMP-Free (NF)

### **APPLICATION TYPES**

Bright, Automotive, Aircraft, Upholstery

### **TYPICAL SPECIFICATIONS**

**TOTAL SOLIDS:** 34 - 36

**pH:** 8.0 - 10.0

**VISCOSITY @ 25 DEGREES C:** 1 - 1000 cps.

**VOC (% OF TOTAL WEIGHT):** 8.0-8.3

**SPECIFIC GRAVITY:** 1.01-1.04

**APPEARANCE:** Opaque

**GLOSS @60°:** 85

**FREEZE/THAW CYCLES D2243:** 0

**SHELF LIFE:** Maximum 12 months.

**HARMONIZE TARIFF NUMBER:** 3909.50.6000

---

**Certified to ISO-9001: 2015**

**Union Specialties, Inc.** 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: [union@unionspecialtiesinc.com](mailto:union@unionspecialtiesinc.com) [www.UnionSpecialtiesInc.com](http://www.UnionSpecialtiesInc.com)

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

**Disclaimer:** The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.

---