



**In Union,
there is strength.**



UNITHANE BNS

Revision Date: 07/18

RECOMMENDED FOR USE WITH:
Leather

UNITHANE BNS is a soft, bright and glossy urethane with exceptional clarity which is very suitable for producing imitation patent, brush off and classic "box" type leathers. UNITHANE BNS is characterized by its very glossy appearance, together with excellent flexibility, both wet and dry. When applied on the correct basecoat, films of UNITHANE BNS will surpass 500,000 dry bally and 100,000 wet bally flexes. We recommend using as follows:

Basecoat Leather and Plate or Rotopress at 120C then Roll Coat x 3 at 5-6 Grams/Foot

UNITHANE BNS 700

UNITHANE 8118 300

Dyestuff 15 (if needed) Crosslinker 15 (if needed).

SPECIAL FEATURES

NMP Containing

APPLICATION TYPES

Bright, Shoe

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 34 - 36

PH: 8.0 - 10.0

VISCOSITY @ 25 DEGREES C: 10 - 100 cps.

VOC (% OF TOTAL WEIGHT): 8.03

SPECIFIC GRAVITY: 1.04

APPEARANCE: Semi-translucent

GLOSS @60°: 90

FREEZE/THAW CYCLES D2243: 3

SHELF LIFE: Maximum 18 months

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
