



**In Union,
there is strength.**



UNITHANE CDY

Revision Date: 11/19

RECOMMENDED FOR USE WITH:

Leather, Automotive Interiors - Leather

UNITHANE CDY is a water based compact binder system designed for use on both automotive and standard split leathers. It is recommended to add pigment, duller, and if needed, additional thickener before roll coating the base coat. UNITHANE CDY will give excellent physical properties and can be plated after application.

Starting Formulation:

Unithane CDY 64

Duller D-21 18

Pigment 18 (Thickener 7488 can be added if needed)

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Automotive, Aircraft, Upholstery, Shoe, Splits

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 29 - 31

PH: 6.0 - 8.5

VISCOSITY @ 25 DEGREES C: 100 - 500 cps.

VOC (% OF TOTAL WEIGHT): 1.61

SPECIFIC GRAVITY: 1.03

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 18 months

HARMONIZE TARIFF NUMBER: 3906.90.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.