



**In Union,
there is strength.**



UNITHANE F-39 NF

Revision Date: 07/18

RECOMMENDED FOR USE WITH:
Leather

UNITHANE F-39 NF is a medium hard, aliphatic waterborne polyurethane made without NMP. The UNITHANE F-39 NF can be used as a topcoat resin in automotive or other high performance coatings. The UNITHANE F-39 NF can be blended with other Unithanes and additives to get the desired look, feel and physicals required for an automotive topcoat. The UNITHANE F-39 NF has excellent abrasion resistance and flexibility.

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Bright, Upholstery, Shoe, Handbag

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 31 - 33

pH: 8.0 - 10.0

VISCOSITY @ 25 DEGREES C: 50 - 400 cps.

VOC (% OF TOTAL WEIGHT): 9.95

SPECIFIC GRAVITY: 1.05

APPEARANCE: Semi-translucent

GLOSS @60°: 88

FREEZE/THAW CYCLES D2243: 3

SHELF LIFE: Maximum 18 months.

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
