



**In Union,
there is strength.**



UNITHANE FSB

Revision Date: 03/19

RECOMMENDED FOR USE WITH:
Leather

UNITHANE FSB is a NMP-Free compact binder, which is designed for use as a basecoat on soft patent leather for both corrected and full grain leathers. UNITHANE FSB has excellent fill and coverage while maintaining a smooth flexible coating. UNITHANE FSB can be used on light colored leathers due to its excellent UV stability and heat resistance. UNITHANE FSB can be applied by either roll-coat or spray.

SPECIAL FEATURES

NMP-Free (NF), Low VOC (<100 g/L)

APPLICATION TYPES

Dull, Shoe, Splits, Handbag, Synthetic Leather

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 24 - 26

pH: 8.0 - 10.0

VISCOSITY @ 25 DEGREES C: 500 - 1000 cps.

VOC (% OF TOTAL WEIGHT): 3.09

SPECIFIC GRAVITY: 1.03

APPEARANCE: Opaque

FREEZE/THAW CYCLES D2243: 0 cycles

SHELF LIFE: Maximum 12 months

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
