



**In Union,
there is strength.**



UNITHANE UDM NF

Revision Date: 01/20

RECOMMENDED FOR USE WITH:
Leather

UNITHANE UDM NF is a medium-soft, NMP-free, waterborne polyurethane topcoat, which will give excellent physical testing results without the use of external cross-linking agents. UNITHANE UDM NF dries to a dull matte with excellent flexibility and Taber abrasion resistance. UNITHANE UDM NF will also give excellent wet veslic and wet crock results when applied in the proportion of 1:1 with water.

Recommended Application (Spray ONE or TWO Cross Coats):

UNITHANE UDM NF 100 Parts

WATER 100 Parts

SPECIAL FEATURES

NMP-Free (NF)

APPLICATION TYPES

Dull, Aircraft, Upholstery, Shoe, Handbag, Synthetic Leather

TYPICAL SPECIFICATIONS

TOTAL SOLIDS: 28.0 - 30.5

pH: 8.0 - 10.0

VISCOSITY @ 25 DEGREES C: 550 - 750 cps.

VOC (% OF TOTAL WEIGHT): 7.70

SPECIFIC GRAVITY: 1.03

APPEARANCE: Opaque

GLOSS @60°: 1.5-3.0

FREEZE/THAW CYCLES D2243: 0

SHELF LIFE: Maximum 18 months

MIX WELL BEFORE USING

HARMONIZE TARIFF NUMBER: 3909.50.6000

Certified to ISO-9001: 2015

Union Specialties, Inc. 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: union@unionspecialtiesinc.com www.UnionSpecialtiesInc.com

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

Disclaimer: The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.
