



**In Union,  
there is strength.**



## UNITHANE UDM

Revision Date: 07/18

**RECOMMENDED FOR USE WITH:**  
Leather

UNITHANE UDM is a medium-soft, waterborne polyurethane topcoat, which will give excellent physical testing results without the use of external cross-linking agents. UNITHANE UDM dries to a dull matte with excellent flexibility and Taber abrasion resistance. UNITHANE UDM will also give excellent wet veslic and wet crock results when applied in the proportions of 1:1 with water.

\* NOTE: THIS PRODUCT MUST BE MIXED THOROUGHLY BEFORE USING.

Recommended Application (Spray ONE or TWO Cross Coats):

UNITHANE UDM 100 Parts

WATER 100 Parts

### SPECIAL FEATURES

NMP Containing, Low VOC (<100 g/L)

### APPLICATION TYPES

Dull, Aircraft, Upholstery, Shoe, Handbag, Synthetic Leather

### TYPICAL SPECIFICATIONS

**TOTAL SOLIDS:** 28 - 30.5

**PH:** 8.0 - 10.0

**VISCOSITY @ 25 DEGREES C:** 550 - 750 cps.

**VOC (% OF TOTAL WEIGHT):** 8.09

**SPECIFIC GRAVITY:** 1.03

**APPEARANCE:** Opaque

**FREEZE/THAW CYCLES D2243:** 0

**SHELF LIFE:** Maximum 18 months

**HARMONIZE TARIFF NUMBER:** 3909.50.6000

---

**Certified to ISO-9001: 2015**

**Union Specialties, Inc.** 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: [union@unionspecialtiesinc.com](mailto:union@unionspecialtiesinc.com) [www.UnionSpecialtiesInc.com](http://www.UnionSpecialtiesInc.com)

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

**Disclaimer:** The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.

---