



**In Union,  
there is strength.**



## UNIWAX PSD

Revision Date: 07/18

**RECOMMENDED FOR USE WITH:**  
Leather

UNIWAX PSD is a wax designed for use in hot roll application on leather to produce a dark, almost black pull-up effect. Results might vary depending on the origin of the crust. UNIWAX PSD is recommended to be applied with a roller coating machine at temperatures above 80°C in its liquid state. As a standard, two coats of 7 - 8 grams per square foot each are applied with passing the leather through a heated drying tunnel above 85°C after each coat. After applying UNIWAX PSD, the leather is left overnight. Next day, the leather can be plated or passed through a rotopress.

### APPLICATION TYPES

Upholstery, Shoe, Handbag

### TYPICAL SPECIFICATIONS

**APPEARANCE:** Off-white Solid Wax

**SHELF LIFE:** Maximum 5 years.

**HARMONIZE TARIFF NUMBER:** 2712.90.0000

---

**Certified to ISO-9001: 2015**

**Union Specialties, Inc.** 3 Malcolm Hoyt Drive, Newburyport, Massachusetts USA

Phone: 978-465-1717 Fax: 978-465-4194 email: [union@unionspecialtiesinc.com](mailto:union@unionspecialtiesinc.com) [www.UnionSpecialtiesInc.com](http://www.UnionSpecialtiesInc.com)

Copyright © 2013-2014 Union Specialties, Inc. All rights reserved, all pages.

**Disclaimer:** The information and data contained herein are believed to be correct. However, we do not warrant either expressly or by implication the accuracy thereof.

---